



公差/General Tolerances(mm)		公差/General Tolerances(mm)										公差/General Tolerances(mm)														
0	>3	>5	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10													
~	3	~	10	~	18	~	30	~	50	~	80	~	120	~	180	~	250	~	315	~	400	~	500	~	>500	0.1/10
±0.12		±0.18		±0.22		±0.26		±0.31		±0.37		±0.57		±0.80		±1.05		±1.15		±1.60		±2.20		±2.50		±Z

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	300/15	300/15	300/10
EC 标准/EC Standard:			
过压类别/Overvoltage Category/污染等	III/3	/	/
级/Pollution Degree			
额定电压/电压/Rated Voltage(V)/Current(A)	500/17.5	/	/
额定冲击电压(KV)/Rate Impulse Voltage(KV)	6.0	/	/
线径范围(硬线和导线)/Wire Range(rigid and flexible)(mm²/AWG)	0.14~1.5/26~14		
间距/Pitch(mm)	3.5		
剥线长度/Stripping length(mm)	8-10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: / SURFACE: /

MAI NO.: /

STATUS: /

APPD: Li GL 2020.03.27

CHKD: Moo J 2020.03.27

DRFT: LiuZH 2019.03.18

SIZE: A4

TYPE: CUSTOMER DRAWING

SCALE: 2:1

ITEM	NAME OF PART	MATERIAL	NOTES	REV	ECN	DESCRIPTION	DRFT	DATE
4	Current carrier	Copper	Sn plated					
3	Spring	Stainless steel	UL94V-0					
2	Button	PA66-GF	UL94V-0					
1	Housing	PA66	UL94V-0					
1	NAME OF PART	MATERIAL	NOTES	REV	ECN	DESCRIPTION	DRFT	DATE

**DEGSON**® NINGBO DEGSON ELECTRICAL CO., LTD  
 宁波高松电子有限公司  
 DRAWING NO.: DS1.5-C01  
 NAME: DS1.5-01P-1Y-00A&Z(H)  
 TYPE: CUSTOMER DRAWING  
 SCALE: 2:1  
 SHEET 1/1