

E27 Double Light Specification



Model:	Q16S-1
APP:	V380 Pro
System structure:	Embedded Linux system, ARM chip structure
Chip:	AK3918E V200
Resolution:	3.0MP
Lens	3.6MM
Pan-tilt:	Horizontal: 355° Vertical: 90°
Preset point quantity:	6pcs
Video compression standard	H.264/20FPS
Video format:	PAL
Minimum illumination:	0.01Lux@ (F2.0, VGC ON), 0.1Lux with IR
Electronic shutter:	Auto
Backlight compensation:	Support
Noise reduction:	2D、3D
Infrared LED:	4pcs infrared LED + 4pcs White LED
Network connection:	Support WIFI, AP hotspot (without RJ45 Network port)
Network:	Wi-Fi (Support IEEE802.11b/g/ N wireless protocol)
Night Version:	Dual Light switch automatic, 5-10 Meters (varies from environment)
Audio:	Built-in microphone and speaker, support two-way real-time audio transmission. ADPCM audio compression standard, self-adaptive stream
Network protocol:	TCP/IP、UDP、HTTP、DNS、DHCP、FTP、NTP
Alarm:	①Motion detection, picture push ②Human intrusion Detection (optional) ③ Support connect with 433 Alarm
ONVIF:	No
Storage:	TF Card (Max 128G) ; Cloud storage (optional)
Power input:	110-240V (E27 holder)
Work environment:	Working temperature:-10°C ~ + 50°C Working Humidity: ≤95%RH