



示意图
SCHEMATIC

产品规格 Specification

| | | | |
|----|-------------------------------|---|--------------|
| 1 | 零件号 part number | LAS3-19F-11E | |
| 2 | 功能 Function | LAS3-19F-11EM | 复位 Momentary |
| 3 | 额定参数 Switch Rating | LAS3-19F-11EL | 自锁 Latching |
| 4 | 外壳材料 The crust material | 5A 250VAC | |
| 5 | IP DEGREE | STAINLESS STEEL/Copper plated nickel | |
| 6 | 端子类型 Terminal Type | IP67 | |
| 7 | 操作温度 Operating temperature | TAB (2. 8X0. 5) | |
| 8 | 接触电阻 contact resistance | -25℃ ~ +55℃ | |
| 9 | 绝缘电阻 insulating resistance | ≤30mΩ | |
| 10 | 绝缘强度 dielectric strength | ≥100mΩ 500V DC | |
| 11 | 操作压力 operating pressure | 2000 VAC | |
| 12 | LED 额定电压 led rated voltage | 2~4N | |
| 13 | 颜色 LED color | 3V、6V、12V、24V、 110V、220V | |
| 14 | LED 寿命 LED life | Single LED: R、G、Y、B、W Dual LED: R-G、R-B、R-W、R-Y、 G-B、G-Y、G-W、B-W、B-Y Triple LED: R-G-B | |
| | | 50000 小时 | 50000 hours |

| | | |
|----|----|------|
| 版本 | 标示 | 更改描述 |
|----|----|------|

| | |
|--------------------|-------|
| 产品型号: LAS3-19F-11E | 产品料号: |
|--------------------|-------|

| | | | |
|-----------------------|-----|-----|-----|
| 产品系列 Rocker switch | 制图: | 审核: | 核准: |
| 图纸比例: 1:1 | 日期: | 日期: | 日期: |

若没有特别标示, 公差依照以下要求:
X、±0.5 . X±0.30 . X±0.15