

Model		SC-180-12		SC-180-24	
	DC voltage	CH1:12V	CH2:13.8V	CH1:24V	CH2:27.6V
	Voltage tolerance	±2%		±1%	
	Rated current	13.5A	1.5A	6.5A	1A
	Current range	0~15A		0~7.5A	
	Rated power	182.7W		182.7W	
	Ripple&noise	120mvp-p		180mvp-p	
output	DCvoltage ADJ.range	CH1:10.3~13.8V		CH1:21.3~27.5V	
	Voltage range	90~132VAC/ 180VAC~264VAC Select by switch ,237~370VDC			
	frequency	47~63HZ			
	AC current	4A/115VAC,2.5A/230VAC			
	efficiency	81%		83%	
input	Inrush current	Cold start current 30A/115VAC,50A/230VAC			
	Leakage current	< 1mA/240VAC			
	Over load	Rated output power110%~150% start over load protection			
		protection mode: AC charging mode:hiccup mode auto-recovery after fault condition is removed			
protection	Battery protection	9.5~11V		20~22V	
	At low voltage	protection mode:cutoff output			
Function	UPS introduction	long-term online floating charge to battery,high charging efficiency,battery can saturate to more than 90% ,cauto-stop charging			
		when it's full,prevent over charging. Effectively extend battery life,AC/battery auto switch,no switch time,no need human guard,			
		cold-start ,when there is no AC input ,can use battery start UPS,Meet the user's emergency needs			
	safety	Withstand voltage	I/P-O/P:3KVAC I/P-FG:1.5KVAC O/P-FG:0.5KVAC		
		Isolated resistance	I/P-O/P,I/P-FG,O/P-FG:100M ohms/500VDC		
Fitstandard	Safety standard	Compliance to UL60950-1			
	EMC standard	Compliance to EN55022,CLASSB			
others	Dimension	199*98*38mm (L*W*H)			
	Weight/packing	0.6kg/45pcs/26kg/0.041m ³ ;1.45CUFT			