





MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.

INSULATION MATERIAL: VINYL **TERMINAL MATERIAL:** COPPER

INSULATION COLOR:22-16A.W.G.: RED  16-14A.W.G.: BLUE 14-12A.W.G.: BLACK  12-10A.W.G.: YELLOW **0.5~1.5mm²(22~16A.W.G.) I Max=19A T Size:0.75mm**

Item No.	Dimension							Color
		d2	W	L	F	E	D	
			mm	mm	mm	mm	mm	
SV1.25-3	#4	3.2mm	5.7	21.2	6.5	10.3	4.3	Red 
SVS1.25-3.5	#6	3.7mm	5.7	21.2	6.5			
SVL1.25-3.5	#6	3.7mm	6.4	21.2	6.5			
SVS1.25-4	#8	4.3mm	6.4	21.2	6.5			
SVM1.25-4	#8	4.3mm	7.2	21.2	6.5			
SVL1.25-4	#8	4.3mm	8.1	21.2	6.5			
SVS1.25-5	#10	5.3mm	8.1	21.2	6.5			
SVL1.25-5	#10	5.3mm	9.5	21.2	6.5			
SVS1.25-6	1/4	6.5mm	9.5	21.2	6.5			
SVL1.25-6	1/4	6.5mm	12.0	27.2	11.0			

1.5~2.5mm²(16~14A.W.G.) I Max=27A T Size:0.80mm

Item No.	Dimension							Color
		d2	W	L	F	E	D	
			mm	mm	mm	mm	mm	
SV2-3	#4	3.2mm	5.7	21.2	6.5	10.3	4.9	Blue 
SVS2-3.5	#6	3.7mm	5.7	21.2	6.5			
SVL2-3.5	#6	3.7mm	6.4	21.2	6.5			
SVS2-4	#8	4.3mm	6.4	21.2	6.5			
SVM2-4	#8	4.3mm	7.2	21.2	6.5			
SVL2-4	#8	4.3mm	8.1	21.2	6.5			
SVS2-5	#10	5.3mm	8.1	21.2	6.5			
SVL2-5	#10	5.3mm	9.5	21.2	6.5			
SVS2-6	1/4	6.5mm	9.5	21.2	6.5			
SVL2-6	1/4	6.5mm	12.0	27.2	11.0			