

Digital Clamp Meter - True RMS

# MS2103A



- Frequency: 2000Hz
- True RMS
- Relative
- 600mA Fuse
- Diode
- Continuity Check
- Non-Contact Voltage (NCV) Detection / Live Wire (Live) Recognition
- Max Display: 6000
- CAT III 600V
- Input Impedance  $\geq 10M\Omega$
- Max Jaw Opening: 19mm
- Auto Power Off
- Data Hold
- Backlight
- Unit Display
- Battery: 1.5V AAA\*2

MS2103A

Spec	Range	Accuracy
Resistance	600 $\Omega$	$\pm(1.0\%+10)$
	6K $\Omega$ , 60K $\Omega$ , 600K $\Omega$ , 6M $\Omega$	$\pm(0.8\%+5)$
	60M $\Omega$	$\pm(2.0\%+10)$
DC Voltage	600mV	$\pm(0.7\%+5)$
	6V, 60V, 600V	$\pm(0.8\%+5)$
AC Voltage	6V, 60V, 600V	$\pm(1.0\%+5)$
	6mA, 60mA, 600mA	$\pm(1.5\%+10)$
DC Current	60A, 200A	$\pm(2.5\%+10)$
	6mA, 60mA, 600mA, 60A, 200A	$\pm(2.5\%+10)$
Capacitance	60nF	$\pm(4.0\%+25)$
	600nF ~ 600uF	$\pm(4.0\%+15)$
	6mF ~ 60mF	$\pm(5.0\%+25)$
Frequency	10Hz ~ 1MHz	$\pm(0.5\%+2)$

Packaging Information	
Accessories	Carry bag, Test leads, Manual, 1.5V*2 AAA Battery
Dimension	60mm*178mm*32mm
Weight	165g
Quantity	40
Color Box	75mm*55mm*195mm
Carton Box	400mm*315mm*395mm
SKU No.	MS2103ACBGLO
EAN Code	8435394788395

**MGL Global Solutions (China) Company Limited**

R72, Puxing East Road, Qingxi, Dongguan, Guangdong, China  
 400-099-1987  
 cs@mastech.cn



WeChat Official Account

[www.mastech-group.com](http://www.mastech-group.com)