

Digital Multimeter - True RMS

# MS850D



- Buzzer / Continuity Check
- Diode
- Transistor Test (Optional Conversion Socket)
- Transistor Test
- MAX / MIN
- True RMS
- REL
- Non-Contact Voltage (NCV) Detection / Live Wire (Live) Recognition
- Max Display: 6000
- CAT III 600V
- Input Impedance
- Auto Power Off
- Data Hold
- Flashlight
- Battery: 1.5V AAA\*2

MS850D

Spec	Range	Accuracy	Spec	Range	Accuracy	
Resistance	600Ω, 6KΩ, 60KΩ, 600KΩ, 6MΩ	±(1.0%+5)	Capacitance	60nF	±(4.0%+25)	
	60MΩ	±(1.2%+8)		600nF, 6μF, 60μF, 600μF	±(4.0%+15)	
DC Voltage	600mV, 6V	±(0.5%+3)	Duty Cycle	0.1% ~ 99.9% (Typical Value Vrms=1V, f=1)	±(1.2%+3)	
	60V	±(0.8%+3)		°C	-20 °C ~ 0 °C	±4°C
	600V	±(0.8%+5)			0 °C ~ 400 °C	±(2.0%+3)
AC Voltage	600mV, 6V, 60V, 600V	±(1.0%+10)	400 °C ~ 1000 °C	±(3.0%+3)		
	DC Current	600uA, 6000uA, 60mA	±(1.0%+5)	°F	-4 °F ~ 50 °F	±5 °F
600mA		±(2.0%+5)	50 °F ~ 750 °F		±(2.0%+5)	
6A, 10A		±(3.0%+5)	750 °F ~ 1832 °F	±(3.0%+5)		
AC Current	600uA, 6000uA, 60mA	±(1.8%+5)				
	600mA	±(2.5%+5)				
Frequency	6A, 10A	±(3.0%+5)				
	10Hz, 100Hz, 1KHz, 10KHz, 100KHz, 1MHz, 10MH	±(0.5%+4)				

Packaging Information	
Accessories	Test leads, Manual, Temperature probe, 1.5V*2 AAA Battery
Dimension	235mm*96mm*46mm
Weight	284g
Quantity	40
Color Box	112mm*54mm*155mm
Carton Box	495mm*310mm*465mm
SKU No.	MS850DCBGLO
EAN Code	8435394788548

**MGL Global Solutions (China) Company Limited**

R72, Puxing East Road, Qingxi, Dongguan, Guangdong, China  
400-099-1987  
cs@mastech.cn



WeChat Official Account

[www.mastech-group.com](http://www.mastech-group.com)