

Digital Multimeter - True RMS

MS890C+



- Frequency: 1000Hz
- True RMS
- Duty Cycle
- Square Wave Output
- Overload Protection
- Diode / Continuity Check
- LED
- Bar Graph
- V.F.C
- Non-Contact Voltage (NCV) Detection / Live Wire (Live) Recognition
- Max Display: 6000
- CAT IV 600V / CAT III 1000V
- Relative / Low Impedance
- Auto Power Off / Data Hold / Backlight / Flashlight
- Unit Display
- Battery: 1.5V AA*2



Spec	Range	Accuracy	Spec	Range	Accuracy
Resistance	600Ω, 6KΩ, 60KΩ, 600KΩ, 6MΩ	±(0.8%+3)	AC Current	60mA, 600mA	±(1.5%+5)
	60MΩ	±(1.0%+25)		6A, 10A	±(1.0%+10)
DC Voltage	600mV, 6V, 60V, 600V	±(0.5%+2)	Capacitance	60nF	±(4.0%+25)
	1000V	±(0.7%+10)		600nF ~ 600uF	±(4.0%+15)
AC Voltage	6V, 60V, 600V	±(0.8%+3)	Frequency	6mF ~ 60mF	±(5.0%+25)
	750V	±(1.0%+5)		1Hz ~ 10MHz	±(0.1%+2)
V-Lowz	600V	DC ±(0.5%+10)	°C	-20 °C ~ 400 °C	±(2.0%+3)
		AC ±(0.8%+10)		400 °C ~ 1000 °C	±(2.0%+3)
DC Current	600uA	±(1.0%+5)	°F	0 °F ~ 1800 °F	±(3.0%+3)
	6mA, 60mA, 600mA	±(0.8%+5)			
	10A	±(1.0%+10)			

Packaging Information	
Accessories	Test leads, Manual, Temperature probe, 1.5V*2 AA Battery
Dimension	185mm*88mm*54mm
Weight	355g
Quantity	20
Color Box	118mm*58mm*195mm
Carton Box	460mm*310mm*345mm
SKU No.	MS890C+CBGLO
EAN Code	8435394788357

MGL Global Solutions (China) Company Limited

R72, Puxing East Road, Qingxi, Dongguan, Guangdong, China
400-099-1987
cs@mastech.cn



WeChat Official Account

www.mastech-group.com